

OpenAir™

Air damper actuators

GDB..1E



Electronic motor driven actuators for open-close, three-position and modulating control

- Nominal torque 5 Nm
- Operating voltage AC 24 V ~ / DC 24...48 V $\overline{\text{=}}$ or AC 100...240 V ~
- Mechanically adjustable span between 0...90°
- Pre-wired with 0.9 m long connection cables
- Type-specific variations with adjustable offset and span for the positioning signal
- Position indication: mechanical and electrical
- Feedback potentiometer
- Self-adaption of rotational angle range and adjustable auxiliary switches for supplementary functions

The rotary actuators are used in ventilation and air conditioning plants to regulate and shut off air dampers:

- For damper areas up to 0.8 m^2 (guideline, always observe damper manufacturer's data).
- Suitable for use with modulating controllers (DC 0/2...10 V), open-close or three-position controllers for air dampers or air throttles.
- We recommend a minimum pulse length of 500 ms on rotary actuators operated with 3-point control to ensure continuous and accurate operation.

Functions

GDB..	AC 24 V ~ / DC 24...48 V $\overline{\text{m}}$	141.1E / 142.1E / 146.1E	161.1E / 163.1E / 164.1E / 166.1E
	AC 100...240 V ~	341.1E / 346.1E	361.1E
Control type		Open-close / three-position	Modulating control (0/2...10 V)
Rotary direction		Clockwise or counter-clockwise direction depends on the type of control ... on the setting of the rotary direction switch. CW  CCW  With no power applied, the actuator remains in the respective position.	
			... on the setting of the rotary direction DIL switch CW  CCW  ... on the positioning signal. The actuator remains in the achieved position: ... if the control signal is maintained at a constant value ... for loss of operating voltage.
Position indication: Mechanical		Rotary angle position indication by using a position indicator.	
Position indication: Electrical		The feedback potentiometer can be connected to external voltage to indicate the position.	Output voltage $U = \text{DC } 0/2...10 \text{ V}$ is generated proportional to the rotary angle. U depends on the rotary direction of the DIL switch setting.
Auxiliary switch		The switching points for auxiliary switches A and B can be set independent of each other in increments of 5° within 0° to 90° .	
Self-adaptation of linear span			When self-adaptation is active, the actuator automatically determines the mechanical end positions of the linear span and maps the characteristic function ($U_0, \Delta U$) to the calculated linear span.
Manual adjustment		The actuator can be manually adjusted by pressing the gear train disengagement button.	
Rotary angle limitation		The rotary angle of the shaft adapter can be limited mechanically with a set screw.	

Technical design

Housing

The housing consists essentially of flame retardant, non brominated, non chlorinated glass fibre reinforced plastic.

Actuator motor / Gears

- Brushless, robust DC motors ensure reliable operation regardless of load. The damper actuators do not require an end position switch, are overload proof, and remain in place upon reaching the end stop.
- The gears are maintenance free and low noise.

Type summary

Type	Stock no.	Control	Operating voltage	Positioning signal Y	Position indicator U = DC 0...10 V $\overline{\text{m}}$	Feedback potentiometer 5 k Ω	Self-adaption of rotational angle range	Aux. switches	Rotary direction switch			
GDB141.1E	S55499-D184	Open-close or three-position	AC 24 V $\sim$ / DC 24...48 V $\overline{\text{m}}$	—	—	—	—	—	yes			
GDB142.1E	S55499-D185					yes		—				
GDB146.1E	S55499-D186		AC 100...240 V $\sim$			—		2				
GDB341.1E	S55499-D187							—				
GDB346.1E	S55499-D188							2				
GDB161.1E	S55499-D266	Modulating	AC 24 V $\sim$ / DC 24...48 V $\overline{\text{m}}$	DC 0/2...10 V $\overline{\text{m}}$	yes	—	yes	—	yes			
GDB163.1E	S55499-D267			DC 0...35 V $\overline{\text{m}}$	yes		yes					
GDB164.1E	S55499-D268			DC 0...35 V $\overline{\text{m}}$	yes		yes			2		
GDB166.1E	S55499-D269			DC 0/2...10 V $\overline{\text{m}}$	yes		yes	—				
GDB361.1E	S55499-D189		AC 100...240 V $\sim$	DC 0/2...10 V $\overline{\text{m}}$	yes		yes	—				

Nominal torque: 5 Nm (applies to all GDB..1E actuators)

Accessories

See data sheet N4698

Product documentation

Topic	Title	Document ID
Data sheet	Air damper actuators	A6V10636149_en--_a
Technical basics	Rotary damper actuators without spring return GD..E	A6V10636139_en--_a
Mounting instructions	GDB..1E, GLB..1E	A6V10636143_----_a

Related documents such as environmental declarations, CE declarations, etc., can be downloaded at the following Internet address:

<http://siemens.com/bt/download>

Notes

Safety

	⚠ Caution
	National safety regulations Failure to comply with national safety regulations may result in personal injury and property damage. • Observe national provisions and comply with the appropriate safety regulations. • Use only properly trained technicians for mounting, commissioning, and servicing.

Potentiometer and auxiliary switches

Potentiometer and auxiliary switches cannot be added in the field

Installation

	⚠ WARNING
No internal line protection for supply lines to external consumers	
Risk of fire and injury due to short-circuits	
Adapt the line diameters as per local regulations to the rated value of the installed fuse.	

Maintenance

The actuators GDB..1E are maintenance-free.

Disposal

	The device is considered an electronics device for disposal in terms of European Directive 2012/19/EU and may not be disposed of as domestic garbage. - Dispose of the device through channels provided for this purpose. - Comply with all local and currently applicable laws and regulations..
---	---

Technical data

Power supply (GDB1..1E)		
Operating voltage (SELV/PELV) / Frequency		AC 24 V ~ ±20 % (19.2...28.8 V ~) / 50/60 Hz DC 24...48 V = ±20 % (19.2...57.6 V =) ¹⁾
Power consumption running	GDB14..1E, GDB16..1E	2 VA / 1 W 2.1 VA / 1.2 W
Power consumption holding	GDB14..1E, GDB16..1E	0.5 W 0.7 W
Power supply (GDB3..1E)		
Operating voltage / Frequency		AC 100...240 V ~ ±10 % (90...264 V ~) / 50/60 Hz
Power consumption running	GDB34..1E, GDB36..1E	5 VA / 1.6 W 3.3 VA / 1.2 W
Power consumption holding	GDB34..1E, GDB36..1E	0.9 W 0.5 W
Function data		
Nominal torque	5 Nm	
Maximum torque (blocked)	10 Nm	
Minimum holding torque	5 Nm	
Nominal rotary angle (with position indication)	90°	
Maximum rotary angle (mechanic limitation)	95° ± 2°	
Runtime for 90° rotary angle	150 s	
Actuator sound power level	28 dB(A)	

¹⁾ C-UL: Permitted only to DC 30 V =

Inputs		
Positioning signal for GDB14..1E		
Operating voltage	(wires 1-6/G-Y1)	clockwise
AC 24 V ~ / DC 24...48 V ≐	(wires 1-7/G-Y2)	counterclockwise
Positioning signal for GDB34..1E		
Operating voltage	(wires 4-6/N-Y1)	clockwise
AC 100...240 V ~	(wires 4-7/N-Y2)	counterclockwise
Positioning signal for GDB16..1.E		
Input voltage	(wires 8-2/Y-G0)	DC 0/2...10 V ≐
Current consumption		0.1 mA
Input resistance		>100 kΩ
Max. permissible input voltage		DC 35 V ≐ limited to DC 10 V ≐
Protected against faulty wiring		max. AC 24 V ~ / DC 24...48 V ≐
Hysteresis	for non-adjustable characteristic function for adjustable characteristic function	60 mV 0.6 % of ΔU
Adjustable characteristic function (GDB163.1E, GDB164.1E)		
Adjustable with 2 potentiometers:	Offset U ₀ Span ΔU	DC 0...5 V ≐ DC 2...30 V ≐ DC 35 V ≐
Max. input voltage		max. AC 24 V ~ / DC 24...48 V ≐
Protected against faulty wiring		
Outputs		
Position indicator		
Output signal (GDB16..1E)	(wires 9-2/U-G0)	DC 0...10 V ≐ DC ±1 mA max. AC 24 V ~ / DC 24...48 V ≐
Output signal (GDB36..1E)	(wires 9-2/U-G-)	
Output voltage U		
Max. output current		
Protected against faulty wiring		
Aux. power supply (G- / G+)		DC 24 V ≐ ±20 %, max. 10 mA
GDB36..		
Feedback potentiometer (for GDB142.1E)		
Change of resistance	(wires P1-P2)	0...5000 Ω
Load		<0.25 W
Max. sliding contact current		<10 mA
Permissible voltage at potentiometer (SELV/PELV)		AC 24 V ~ / DC 24...48 V ≐
Insulation resistance between potentiometer and housing		AC 500 V ~
Auxiliary switches (GDB146.1E, GDB166.1E, GDB346.1E)		
Switching voltage		AC 24...250 V ~ / DC 12...30 V ≐
Contact rating		6 A resistive, 2 A inductive, min. 10 mA @ AC 4 A resistive, 2 A inductive, min. 10 mA @ DC 30 V ≐ 0.8 A res., 0.5 A inductive, min. 10 mA @ DC 60 V ≐
Electric strength auxiliary switch against housing		AC 4 kV
Switching range for auxiliary switches / setting increments		5°...90° / 5°
Factory switch setting:	Switch A	5°
	Switch B	85°
Connection cables		
Cable length		0.9 m
Cross section of prewired connection cables		0.75 mm ²
Permissible length for signal lines		300 m
Degree of protection		
Insulation class		As per EN 60730
AC 24 V ~ / DC 24...48 V ≐, feedback potentiometer		III
AC 100...240 V ~, auxiliary switches		II
Housing protection		IP 54 as per EN 60529



Environmental conditions	
Operation	IEC 60721-3-3
Climatic conditions	Class 3K5
Mounting location	interior, weather-protected
Temperature extended	-32...+55 °C
Humidity (non-condensing)	<95 % r.F.
Transport	IEC 60721-3-2
Climatic conditions	Class 2K3
Temperature extended	-32...+70 °C
Humidity (non-condensing)	<95 % r.F.
Storage	IEC 60721-3-1
Climatic conditions	Class 1K3
Temperature extended	-32...+50 °C
Humidity (non-condensing)	<95 % r.F.
Mechanical conditions	Class 2M2
Standards, directives and approvals	
Product standard	EN 60730 Part 2-14 / Particular requirements for electric actuators
Electromagnetic compatibility (Applications)	For use in residential, commercial, light-industrial and industrial environments
EU Conformity (CE)	A5W00003842 ²⁾
RCM Conformity	A5W00003843 ²⁾
EAC Conformity	Eurasian conformity
UL	UL as per UL 60730 http://ul.com/database cUL as per CSA-C22.2 No. 24-93
Environmental compatibility	
The product environmental declaration A5W00026066 ²⁾ contains data on environmentally compatible product design and assessments (RoHS compliance, materials composition, packaging, environmental benefit, disposal).	
Dimensions	
Actuator W x H x D	see „Dimensions“, p. 9
Damper shaft	
round	8...16 mm
round	8...10 mm (with centering element)
Square	6...12.8 mm
Min. shaft length	20 mm
Shaft hardness	<300 HV
Weight	
Without packaging	Max. 0.49 kg, without switches Max. 0.63 kg, with switches

²⁾ The documents can be downloaded from <http://siemens.com/bt/download>.

Internal Diagrams

GDB14..1E (open-close, three-p.)




GDB34..1E (open-close, three-p.)



GDB16..1E (modulating, Y= DC 0/2...10 V ~)


GDB16..1E (modulating, Y= DC 0...35 V ~)

GDB361.1E (modulating control)



Connection diagrams

GDB1..1E (AC 24 V ~ / DC 24...48 V ~)




Open-close, single wire control Single Pole Single Throw (SPST)	Open-close, two wire control Single Pole Double Throw (SPDT)	Three-position control	Modulating control

Cable labeling

Connection	Code	No	Color	Abbreviation	Meaning
Actuators	G	1	red	RD	System potential AC 24 V ~ / DC 24...48 V =
AC 24 V ~	G0	2	black	BK	System neutral
DC 24...48 V =	Y1	6	purple	VT	Positioning signal AC/DC 0 V, "clockwise" (GDB14..1E)
	Y2	7	orange	OG	Positioning signal AC/DC 0 V, "counter-clockwise" (GDB14..1E)
	Y	8	grey	GY	Signal in (GDB16..1E)
	U	9	pink	PK	Signal out (GDB16..1E)
Actuators	L	3	brown	BR	Line AC 100...240 V ~
AC 100...240 V ~	N	4	light blue	BU	Neutral conductor
	Y1	6	black	BK	Positioning signal AC 100...240 V ~, "clockwise" (GDB34..1E)
	Y2	7	white	WH	Positioning signal AC 100...240 V ~, "counter-clockwise" (GDB34..1E)
	G+	1	red	RD	System potential DC 24 V = (aux. power supply) (GDB361.1E)
	G-	2	black	BK	System neutral (aux. power supply) (GDB361.1E)
	Y	8	grey	GY	Signal in (GDB361.1E)
	U	9	pink	PK	Signal out (GDB361.1E)
Feedback potentiometer	a	P1	white/red	WH RD	Potentiometer 0...100 % (P1-P2)
	b	P2	white/blue	WH BU	Potentiometer pick-off
	c	P3	white/pink	WH PK	Potentiometer 100...0 % (P3-P2)
Auxiliary switch	Q11	S1	grey/red	GY RD	Switch A input
	Q12	S2	grey/blue	GY BU	Switch A normally closed contact
	Q14	S3	grey/pink	GY PK	Switch A normally open contact
	Q21	S4	black/red	BK RD	Switch B input
	Q22	S5	black/blue	BK BU	Switch B normally closed contact
	Q24	S6	black/pink	BK PK	Switch B normally open contact

Dimensions



Dimensions in mm

Revision numbers

Type	Valid from rev. no.	Type	Valid from rev. no.
GDB141.1E	..B	GDB164.1E	..B
GDB142.1E	..B	GDB166.1E	..B
GDB146.1E	..B	GDB361.1E	..B
GDB161.1E	..B	GDB341.1E	..B
GDB163.1E	..B	GDB346.1E	..B

Issued by
Siemens Switzerland Ltd
Building Technologies Division
International Headquarters
Gubelstrasse 22
6301 Zug
Switzerland
Tel. +41 41-724 24 24
www.siemens.com/buildingtechnologies

© Siemens Switzerland Ltd, 2016
Technical specifications and availability subject to change without notice.

Document ID A6V10636149_en--_b
Issue 2016-12-14